

- Platform Length** : 9000 mm
- Length of gooseneck** : 3850 mm
- Total Width** : 2550 mm (2750mm (3000mm))
- Length Trailer** : 12930 mm
- 5th Wheels Height** : 1300mm
- Loading Platform Height** : 910 mm loaded
- Chassis** : ST 52-3 made of high tensile steel (I) cross-sectioned chassis
- Base** : + 60mm hardwood upper wheel drop patterned sheet
- Brake** : 71/320 / EEC regulations according to EBS 2S / 2M dual circuit brake system comprising antiblocking system electroneutral-pneumatically
- Axles** : 3x12 ton capacity air suspension axles and drum
- Suspension Type** : 3 fixed axle
- Ramp Type** : Mechanical shift pneumatic or hydraulic integrally +
- Tire** : 12 + 1 245/70 / 17.5
- King Pin** : 3,5 " Kingpin + 2 'Kingpin



TR _____

444 5 300

www.odabasi.com.tr

LOWBED



Platform Uzunluęu	: 9000 mm
Deveboynu Uzunluęu	: 3850 mm
Toplam Geniřlik	: 2550 mm (2750mm (3000mm))
Treyler Uzunluęu	: 12930 mm
5.Teker Ykseklięi	: 1300mm
Ykleme Platformu Ykseklięi	: 910 mm ykl
řasi	: Yksek çekme mukavemetli ST 52-3 çelikten imal edil-
miř (I)kesitli řasi	
Taban	: 60mm sert aęaç + tekerlek stleri damla desenli sac
Fren	: 71/320/EEC ynetmelięine uygun EBS 2S / 2M antib-
lokaj sistemi ieren çift devreli elktro-panmatik fren sistemi	
Dingiller	: 3X12 ton kapasiteli hava sspansiyonlu ve kampanalı
dingiller	
Dingil Tipi	: 3 adet Sabit dingil
Rampa Tipi	: Havalı veya hidrolik yekpare + mekanik kaydırmalı
Lastik	: 12+1 adet 245/70/17,5
King Pimi	: 3,5" Kingpin + 2" Kingpin



20

